


LEGENDA:

- Conducta apa rece, PPR /PEHD
- Conducta apa calda, PPR insertie AI
- Conducta apa uzata menajera, PP/PVC
- Conducta condens climatizare PP
- Sp Ø50
- Robinet coltar DN 1/2 "
- CV
- B.E
- Boiler electric , capacitate 10 l

Nota : Dupa efectuarea probelor de presiune la rece si cald ,conductele PPR pentru apa rece , apa calda se vor izola termic cu tuburi de spuma de polietilena avand grosimea de 6 mm.
Conductele de condens se vor racorda la sifonul lavoarului.

Pante normale si minime ale conductelor de legatura			
Punct de consum	Diametrul conductei de legatura [mm]	Panta conductei de legatura	
		normala	minima
Lavoar	32	0,035	0,025
WC	110	0,020	0,012
Sifon de pardoseala	50	0,035	0,025

la CM01
PVC-KG Ø110,i=0,020

VERIFICATOR EXPERT	NUME	SEMNATURA	CERINTA	REFERAT/ EXPERTIZA/ NR./ DATA	
PROIECTANT GENERAL	S.C. STRUCT-EL PROIECT S.R.L. BUDACU DE JOS			Beneficiar: U.A.T. COMUNA TELCIU SAT TELCIU, NR. 744 B	Proiect nr.
PROIECTANT DE SPECIALITATE	S.C. PLANEX LINE S.R.L. FELDRU			JUD. BISTRITA–NASAUD Titlu proiect: CONSTRUIRE CAPELA MORTUARA COM. TELCIU, SAT BICHIGIU, FN JUD. BISTRITA–NASAUD	23/2025
SPECIFICATIE	NUME	SEMNATURA	Scara	COM. TELCIU, SAT BICHIGIU, FN JUD. BISTRITA–NASAUD	Faza
SEF PROIECT	arh.DEMIAN DA	ANA	1: 50		DTAC+ PT
PROIECTAT	ing.GALAN VIORICA		Data		Plansa nr.
INTOCMIT	ing.GALAN VIORICA		07.2025	Titlu plansa instalatii sanitare	IS02